

Package: etsi (via r-universe)

June 5, 2026

Type Package

Title Efficient Testing Using Surrogate Information

Version 1.0

Date 2025-11-03

Description Provides functions for treatment effect estimation, hypothesis testing, and future study design for settings where the surrogate is used in place of the primary outcome for individuals for whom the surrogate is valid, and the primary outcome is purposefully measured in the remaining patients. More details are available in: Knowlton, R., Parast, L. (2024) "Efficient Testing Using Surrogate Information," Biometrical Journal, 67(6): e70086, <doi:10.1002/bimj.70086>. A tutorial for this package can be found at <<https://www.laylaparast.com/etsi>>.

License GPL

Imports hetsurr, stats

NeedsCompilation no

Author Rebecca Knowlton [aut], Layla Parast [aut, cre]

Maintainer Layla Parast <parast@austin.utexas.edu>

Repository <https://laylaparast.r-universe.dev>

Date/Publication 2025-11-06 10:50:02 UTC

RemoteUrl <https://github.com/cran/etsi>

RemoteRef HEAD

RemoteSha a27baf4f802f7ea3f6cf2151f654ec1a2c6a770b

Contents

| | |
|------------------------|---|
| etsi.design | 2 |
| etsi.main | 3 |
| exampledataA | 4 |
| exampledataB | 5 |

| | |
|--------------|----------|
| Index | 6 |
|--------------|----------|

| | |
|-------------|---|
| etsi.design | <i>Calculates the estimated power for a future Study B or the required sample size to achieve a desired level of power.</i> |
|-------------|---|

Description

Function to help design a future Study B given data from Study A. Depending on the inputs, either calculates the estimated power in Study B, or calculates the required sample size in each treatment group to achieve a desired level of power in Study B.

Usage

```
etsi.design(Study.A, n.b0 = NULL, n.b1 = NULL, psi = NULL, w.range = NULL,
            kappa = NULL, desired.power = NULL, iterations = 100)
```

Arguments

| | |
|---------------|---|
| Study.A | Study.A, a dataframe representing Study A containing the required columns A (treatment assignment), Y (primary outcome), S (surrogate outcome), and W (baseline covariate of interest). Optionally contains a column delta, which is an indicator for strong surrogacy. |
| n.b0 | n.b0, sample size in Study B control group |
| n.b1 | n.b1, sample size in Study B treatment group |
| psi | psi, the overall treatment effect you want to detect in Study B |
| w.range | w.range, a vector containing the lower and upper limits of the covariate W you plan to have in Study B |
| kappa | kappa, the threshold to determine strong surrogacy when the delta columns is not provided in Study.A. Surrogacy is considered sufficiently strong when the estimated PTE with respect to W is greater than kappa. |
| desired.power | The desired power in Study B, when you want to calculate required sample size |
| iterations | The number of iterations used for generalized cross-validation. |

Value

A list is returned:

| | |
|-------------|---|
| power | The estimated power in Study B; only given if desired.power = NULL. |
| sample.size | The required sample size in each treatment group in Study B; only given if desired.power is not NULL. |

Author(s)

Rebecca Knowlton

References

Knowlton, R., Parast, L. (2025) "Efficient Testing Using Surrogate Information." Biometrical Journal, 67(6): e70086.

Examples

```
data(exampladataA)
data(exampladataB)
names(exampladataA)
names(exampladataB)
etsi.design(Study.A = exampladataA,
            n.b0 = 400,
            n.b1 = 500,
            iterations = 10)
```

| | |
|-----------|---|
| etsi.main | <i>Estimates the pooled treatment effect quantity, standard error, and corresponding p-value.</i> |
|-----------|---|

Description

Estimates the pooled treatment effect quantity in Study B, using the surrogate information learned from Study A. Provides the corresponding estimated standard error and p-value for testing the null hypothesis of a treatment effect equal to 0.

Usage

```
etsi.main(Study.A, Study.B, kappa = NULL)
```

Arguments

| | |
|---------|---|
| Study.A | Study.A, a dataframe representing Study A containing the required columns A (treatment assignment), Y (primary outcome), S (surrogate outcome), and W (baseline covariate of interest). Optionally contains a column delta, which is an indicator for strong surrogacy. |
| Study.B | Study.B, a dataframe representing Study B containing the required columns A (treatment assignment), Y (primary outcome), S (surrogate outcome), and W (baseline covariate of interest). Optionally contains a column delta, which is an indicator for strong surrogacy. |
| kappa | kappa, the threshold to determine strong surrogacy when the delta columns are not provided in Study.A and Study.B. Surrogacy is considered sufficiently strong when the estimated PTE with respect to W is greater than kappa. |

Value

A list is returned:

| | |
|-------------------------|---|
| <code>delta.P</code> | The pooled treatment effect quantity for Study B |
| <code>se.delta.P</code> | Standard error of delta.P |
| <code>p.value</code> | p-value for testing the null hypothesis that $\text{delta.P} = 0$ |

Author(s)

Rebecca Knowlton

References

Knowlton, R., Parast, L. (2025) "Efficient Testing Using Surrogate Information." *Biometrical Journal*, 67(6): e70086.

Examples

```
data(exampledataA)
data(exampledataB)
names(exampledataA)
names(exampledataB)
etsi.main(Study.A = exampledataA,
          Study.B = exampledataB)
```

exampledataA

Example Data (Study A)

Description

Example Data (Study A)

Usage

```
data("exampledataA")
```

Format

A data frame with 1000 observations from a treatment group and 1100 observations from a control group:

A the treatment assignment, where 1 indicates treatment and 0 indicates control

W the baseline covariate of interest

S the surrogate outcome

Y the primary outcome

delta the indicator for strong surrogacy, where 1 indicates strong and 0 indicates weak

Examples

```
data(exampledataA)
names(exampledataA)
```

| | |
|--------------|-------------------------------|
| exampledataB | <i>Example Data (Study B)</i> |
|--------------|-------------------------------|

Description

Example Data (Study B)

Usage

```
data("exampledataB")
```

Format

A data frame with 500 observations from a treatment group and 400 observations from a control group:

A the treatment assignment, where 1 indicates treatment and 0 indicates control

W the baseline covariate of interest

S the surrogate outcome

Y the primary outcome

delta the indicator for strong surrogacy, where 1 indicates strong and 0 indicates weak

Examples

```
data(exampledataB)
names(exampledataB)
```

Index

etsi.design, 2
etsi.main, 3
exampledataA, 4
exampledataB, 5