

Package: longsurr (via r-universe)

September 17, 2024

Type Package

Title Longitudinal Surrogate Marker Analysis

Version 1.0

Description Assess the proportion of treatment effect explained by a longitudinal surrogate marker as described in Agniel D and Parast L (2021) <[doi:10.1111/biom.13310](https://doi.org/10.1111/biom.13310)>.

License GPL

Imports stringr, splines, mgcv, Rsurrogate, dplyr, here, tidyr, fs, KernSmooth, stats, fdapace, grf, lme4, mvnfast, plyr, tibble, magrittr, glue, purrr, readr, refund, fda, fda.usc

NeedsCompilation no

Author Layla Parast [aut, cre], Denis Agniel [aut]

Maintainer Layla Parast <parast@austin.utexas.edu>

Depends R (>= 3.5.0)

Date/Publication 2022-09-29 10:00:02 UTC

Repository <https://laylaparast.r-universe.dev>

RemoteUrl <https://github.com/cran/longsurr>

RemoteRef HEAD

RemoteSha 9b2cf16ada01e2d10ae08725f7909eebe5dbca82

Contents

estimate_surrogate_value	2
full_data	3
presmooth_data	4

Index	5
--------------	----------

 estimate_surrogate_value

Estimate the surrogate value of a longitudinal marker

Description

Estimate the surrogate value of a longitudinal marker

Usage

```
estimate_surrogate_value(y_t, y_c, X_t, X_c, method = c("gam", "linear",
  "kernel"), k = 3, var = FALSE, bootstrap_samples = 50, alpha = 0.05)
```

Arguments

y_t	vector of n1 outcome measurements for treatment group
y_c	vector of n0 outcome measurements for control or reference group
X_t	n1 x T matrix of longitudinal surrogate measurements for treatment group, where T is the number of time points
X_c	n0 x T matrix of longitudinal surrogate measurements for control or reference group, where T is the number of time points
method	method for dimension-reduction of longitudinal surrogate, either 'gam', 'linear', or 'kernel'
k	number of eigenfunctions to use in semimetric
var	logical, if TRUE then standard error estimates and confidence intervals are provided
bootstrap_samples	number of bootstrap samples to use for standard error estimation, used if var = TRUE, default is 50
alpha	alpha level, default is 0.05

Value

a tibble containing estimates of the treatment effect (Deltahat), the residual treatment effect (Deltahat_S), and the proportion of treatment effect explained (R); if var = TRUE, then standard errors of Deltahat_S and R are also provided (Deltahat_S_se and R_se), and quantile-based 95% confidence intervals for Deltahat_S and R are provided (Deltahat_S_ci_l [lower], Deltahat_S_ci_h [upper], R_ci_l [lower], R_ci_u [upper])

References

Agniel D and Parast L (2021). Evaluation of Longitudinal Surrogate Markers. *Biometrics*, 77(2): 477-489.

Examples

```
library(dplyr)
data(full_data)

wide_ds <- full_data %>%
  dplyr::select(id, a, tt, x, y) %>%
  tidyr::spread(tt, x)

wide_ds_0 <- wide_ds %>% filter(a == 0)
wide_ds_1 <- wide_ds %>% filter(a == 1)
X_t <- wide_ds_1 %>% dplyr::select(`-1`:`1`) %>% as.matrix
y_t <- wide_ds_1 %>% pull(y)
X_c <- wide_ds_0 %>% dplyr::select(`-1`:`1`) %>% as.matrix
y_c <- wide_ds_0 %>% pull(y)

estimate_surrogate_value(y_t = y_t, y_c = y_c, X_t = X_t, X_c = X_c,
  method = 'gam', var = FALSE)
estimate_surrogate_value(y_t = y_t, y_c = y_c, X_t = X_t, X_c = X_c,
  method = 'linear', var = TRUE, bootstrap_sample = 50)
```

full_data

Example data to illustrate functions

Description

Simulated nonsmooth data to illustrate functions

Usage

```
data("full_data")
```

Format

A data frame with 10100 observations on the following 5 variables.

id a unique person ID
a treatment group, 0 or 1
tt time
x surrogate marker value
y primary outcome

presmooth_data	<i>Pre-smooth sparse longitudinal data</i>
----------------	--

Description

Pre-smooth sparse longitudinal data

Usage

```
presmooth_data(obs_data, ...)
```

Arguments

obs_data	data.frame or tibble containing the observed data, with columns <code>id</code> identifying the individual measured, <code>tt</code> identifying the time of the observation, <code>x</code> the value of the surrogate at time <code>tt</code> , and <code>a</code> indicating 1 for treatment arm and 0 for control arm.
...	additional arguments passed on to <code>fpca</code>

Value

list containing matrices X_t and X_c , which are the smoothed surrogate values for the treated and control groups, respectively, for use in downstream analyses

Examples

```
library(dplyr)
data(full_data)
obs_ds <- group_by(full_data, id)
obs_data <- sample_n(obs_ds, 5)
obs_data <- ungroup(obs_data)

head(obs_data)
presmooth_X <- presmooth_data(obs_data)
```

Index

* **datasets**

full_data, 3

estimate_surrogate_value, 2

full_data, 3

presmooth_data, 4